Product data sheet Characteristics

9065SE08

Overload Relay, Type S, melting alloy, Size 2, 3 pole, 45A maximum, 600 VAC, separate mount, panel mount

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 188.70 USD



Main

| Range of product | Separate Mounting |
|-----------------------|-------------------|
| Thermal overload type | Melting alloy |

Complementary

| , | |
|----------------------------------|--------------------|
| NEMA size | 2 |
| Number of thermal units required | 3 |
| Mounting support | Panel |
| [Ue] rated operational voltage | 600 V AC |
| Maximum Height | 3.31 in (84.1 mm) |
| Maximum Width | 3.50 in (88.9 mm) |
| Maximum Depth | 3.97 in (100.8 mm) |
| | |

Ordering and shipping details

| Main | | |
|---|--|--|
| Range of product | Separate Mounting | |
| Thermal overload type | Melting alloy | |
| 3, | <u>, </u> | |
| 0 | | |
| Complementary | 2 | |
| NEMA size | 2 | |
| Number of thermal units required | 3 | |
| Mounting support | Panel | |
| [Ue] rated operational voltage | 600 V AC | |
| Maximum Height | 3.31 in (84.1 mm) | |
| Maximum Width | 3.50 in (88.9 mm) | |
| Maximum Depth | 3.97 in (100.8 mm) | |
| | | |
| Ordering and shipping details | | |
| Category | 21661 - 9065 A,C,F,G,S(NOT SS) | |
| Discount Schedule | CP1 | |
| GTIN | 00785901893707 | |
| Nbr. of units in pkg. | 1 | |
| Package weight(Lbs) | 1.1 lb(US) (0.50 kg) | |
| Returnability | No | |
| Country of origin | MX | |
| | | |
| Packing Units | | |
| Package 1 Height | 4.70 in (11.938 cm) | |
| | | |
| * Price is "List Price" and may be subject to a trade | discount – check with your local distributor or retailer for actual price. | |

Packing Units

| Package 1 Height | 4.70 in (11.938 cm) |
|------------------|---------------------|

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



| Package 1 width | 5.20 in (13.208 cm) |
|--|---------------------|
| Package 1 Length | 5.30 in (13.462 cm) |
| | |
| | |
| Offer Sustainability | |
| Offer Sustainability EU RoHS Directive | Not compliant |

18 months

Warranty

Contractual warranty