

9080FB1221R

Terminal block, Linergy, fuse holder, Class R,
60A, 250 V, 1 pole

Product availability : Stock - Normally stocked in distribution facility



Price* : 42.60 USD



Main

Range	9080FB
Product	Fuse holder

Complementary

Current Rating	60 A
[Ue] rated operational voltage	<= 250 V AC/DC
Fuse type	R
Fuse size	0.8125 x 3 in
Number of poles	1
Electrical connection	Box lugs
Wire Gauge	AWG 14...AWG 2 copper or aluminium
SCCR	200 kA UL 512
Product certifications	CE UL listed file E40747 CCN IZLT CSA file 70360 class 6225 01
Operating Temperature	-40...257 °F (-40...125 °C)
Mounting Type	Surface mount
Block Material	Thermoplastic block
Wire stripping length	0.5625 in (14.29 mm)
Terminal Tightening Torque	lugs 50 lbf.in (5.65 N.m) AWG 3...AWG 2 copper or aluminium lugs 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper or aluminium lugs 40 lbf.in (4.52 N.m) AWG 8 copper or aluminium lugs 35 lbf.in (3.95 N.m) AWG 12...AWG10 copper or aluminium lugs 35 lbf.in (3.95 N.m) AWG 14 copper
Maximum Height	4.83 in (122.68 mm)
Maximum Width	1.48 in (37.59 mm)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 13, 2020

Maximum Depth	2.01 in (51.05 mm)
---------------	--------------------

Ordering and shipping details

Category	21701 - 9080 FB
Discount Schedule	CP1
GTIN	00785901097808
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Unit Type of Package 2	CAR

Offer Sustainability

REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------