

Product data sheet

Specifications

SQUARE D



Terminal block, Linergy, fuse holder, Class R, 60A, 250V, 1 pole

9080FB1221R

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080FB
Product	Fuse holder

Complementary

Current Rating	60 A
[Ue] rated operational voltage	<= 250 V AC/DC
Fuse type	R
Fuse size	0.8125 x 3 in
Number of poles	1
Electrical Connection	Box lugs
Wire Gauge	AWG 14...AWG 2 copper or aluminium
SCCR	200 kA UL 512
Product Certifications	CE UL listed file E40747 CCN IZLT CSA file 70360 class 6225 01
Operating Temperature	-40...257 °F (-40...125 °C)
Mounting Type	Surface mount
Block Material	Thermoplastic: block
Wire stripping length	0.5625 in (14.2875 mm)
Terminal Tightening Torque	lugs 50 lbf.in (5.6 N.m) AWG 3...AWG 2 copper or aluminium lugs 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper or aluminium lugs 40 lbf.in (4.5 N.m) AWG 8 copper or aluminium lugs 35 lbf.in (4.0 N.m) AWG 12...AWG10 copper or aluminium lugs 35 lbf.in (4.0 N.m) AWG 14 copper
Height	4.83 in (122.68 mm)
Width	1.48 in (37.59 mm)
Depth	2.01 in (51.05 mm)

Ordering and shipping details

Category	US10CP121701
Discount Schedule	0CP1
GTIN	785901097808
Returnability	Yes
Country of origin	US

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.00 in (5.08 cm)
Package 1 Width	1.50 in (3.81 cm)
Package 1 Length	4.800 in (12.192 cm)
Package weight(Lbs)	3.680 oz (104.326 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Height	5.700 in (14.478 cm)
Package 2 Width	10.700 in (27.178 cm)
Package 2 Length	17.00 in (43.18 cm)
Package 2 Weight	11.499 lb(US) (5.216 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

Repack and remanufacture	
Take-back	No

Product data sheet

9080FB1221R

Technical Illustration

Dimensions

