Product data sheet Characteristics

A9XPH212

Acti 9 - comb busbar - 1L+N - 18 mm pitch - 12 modules - 100 A

Product availability: Stock - Normally stocked in distribution facility



Price*: 47.02 USD



Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	12

Complementary

Main		
Range	Acti 9	
Product or component type	Comb busbar	
Accessory / separate part category	Connection accessory	
Lines description	1L + N	
Length in 18 mm modules	12	
Complementary		
Number of ways	6 ways N + 1 L	
Poles configuration for 1 way	1 x 1P + N	
	1 x 2P	
Connection pitch	0.71 in (18 mm)	
Connector type	tooth	
Distance between way	1.42 in (36 mm)	
Marking	N L	
Insulation	Insulated	
Device presentation	Cuttable	
[le] rated operational current	100 A 104 °F (40 °C)	
[Ue] rated operational voltage	415 V AC	
[Ui] rated insulation voltage	500 V AC IEC 61439-2	
Mounting mode	Horizontal	
Mounting location	Top or bottom tunnel type terminals Top or bottom double terminal	
9 mm pitches	24	
Maximum Width	8.66 in (220 mm)	
Color	White RAL 9003)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Range compatibility	Acti 9 iC60
	Acti 9 iK60
	Acti 9 iID
	Acti 9 iID K
	Acti 9 iSW
	Acti 9 iSW-NA
	Multi 9 C60

Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	1760 °F (960 °C) 30 s) IEC 60695-2-1
Pollution degree	3 IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901953142
Nbr. of units in pkg.	1
Package weight(Lbs)	0.17 lb(US) (0.08 kg)
Returnability	Yes
Country of origin	DE

Packing Units

Package 1 Height	0.100 dm	
Package 1 width	0.300 dm	
Package 1 Length	2.120 dm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 18 months

