# Product data sheet Characteristics

# **A9XPH257**

Acti 9 - comb busbar - 1L+N - 18 mm pitch - 57 modules - 100 A

Product availability: Stock - Normally stocked in distribution facility



Price\*: 198.00 USD

#### Main

Range	Acti 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	57

#### Complementary

Main		
Range	Acti 9	
Product or component type	Comb busbar	
Accessory / separate part category	Connection accessory	
Lines description	1L + N	
Length in 18 mm modules	57	
Complementary		
Complementary Number of ways	28 ways N + 1 L	
Poles configuration for 1 way	1 x 1P + N	
Toles configuration for T way	1 x 2P	
Connection pitch	0.71 in (18 mm)	
Connector type	tooth	
Distance between way	1.42 in (36 mm)	
Marking	NL	
Insulation	Insulated	
Device presentation	Cuttable	
Provided equipment	Set of 10 end piece	
[le] rated operational current	100 A 104 °F (40 °C)	
[Ue] rated operational voltage	415 V AC	
[Ui] rated insulation voltage	500 V AC IEC 61439-2	
Mounting mode	Horizontal	
Mounting location	Top or bottom tunnel type terminals Top or bottom double terminal	
9 mm pitches	114	
Maximum Width	39.37 in (1000 mm)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Color	White RAL 9003)	
Range compatibility	Acti 9 iC60 Acti 9 iK60 Acti 9 iK60 Acti 9 iID Acti 9 iID K Acti 9 iSW Acti 9 iSW Acti 9 iSW-NA Multi 9 C60	

### Environment

Standards	IEC 60947-7-1 IEC 61439-2
Fire resistance	1760 °F (960 °C) 30 s ) IEC 60695-2-1
Pollution degree	3 IEC 60947-7-1
IP degree of protection	IP20 with end-pieces and tooth covers

### Ordering and shipping details

ordorning dire ornipping dotaile	
Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901846994
Nbr. of units in pkg.	5
Package weight(Lbs)	0.87 lb(US) (0.39 kg)
Returnability	No
Country of origin	DE

# Packing Units

Package 1 Height	0.100 dm	
Package 1 width	0.300 dm	
Package 1 Length	10.000 dm	

#### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty 18 months
--------------------