

Main

Accessory / separate part category	Mounting accessories
Accessory / separate part type	Notched uprights
Enclosure accessory description	Notched mounting rail
Quantity per Set	Set of 2 Set of 4
Star-delta starter component	Uprights Mounting rails

Complementary

Assembly style	For assembly
Depth	1.0 in (25 mm)
Height	78.7 In (2000 mm) 0.0000000000 in (0 mm)
Horizontal fixing centres	61.02 in (1550 mm)
Length	78.7 in (2000 mm)
Material	Steel coated with zinc chromate
Motor power kW	110 KW 160 KW 185 KW 375 KW 100 KW 220 KW 90 KW 200 KW 250 KW 280 KW 315 kW
Motor starter type	Star-delta starters
Number of devices	1 2
Product Compatibility	For enclosure of width 1600 mm For enclosure of height 1600 mm
Net Weight	5.3 Lb(US) (2.4 kg) 6.57 lb(US) (2.98 kg)
Type of rail	Notched
Surface treatment	Zinc chromate
Thickness	0.08 in (2 mm)
Vertical fixing centres	59.06 in (1500 mm)
Width	0.0000000000 In (0 mm) 63.0 In (1600 mm) 1.6 in (40 mm)

Ordering and shipping details

Category	US1000I22621
Discount Schedule	000I
GTIN	3389110542141
Returnability	No
Country of origin	IT

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.49 in (1.25 cm)
Package 1 Width	2.0 in (5 cm)
Package 1 Length	78.7 in (200 cm)
Package 1 Weight	6.50 lb(US) (2.95 kg)
Unit Type of Package 2	CAR
Number of Units in Package 2	2
Package 2 Height	78.7 in (200 cm)
Package 2 Width	2.0 in (5 cm)
Package 2 Length	1.0 in (2.5 cm)
Package 2 Weight	13.007 lb(US) (5.9 kg)
Unit Type of Package 3	P2M
Number of Units in Package 3	160
Package 3 Height	19.3 in (49 cm)
Package 3 Width	78.7 in (200 cm)
Package 3 Length	47.2 in (120 cm)
Package 3 Weight	1558.7 lb(US) (707 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------