

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 2,079.00 USD



Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Resistive load Motor control
Utilisation category	AC-3 AC-4 AC-1
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	265 A 104 °F (40 °C)) <= 440 V AC AC-3 350 A 104 °F (40 °C)) <= 440 V AC AC-1 245 A 104 °F (40 °C)) <= 440 V AC AC-4
Motor power kW	132 kW 400 V AC 50/60 Hz AC-4)
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	240 V AC 50/60 Hz
Irms rated making capacity	2940 A
Rated breaking capacity	2450 A 220...440 V 2200 A 500 V 800 A 1000 V 1700 A 660/690 V
[Icw] rated short-time withstand current	2200 A 104 °F (40 °C) - 1 s 2200 A 104 °F (40 °C) - 5 s 2200 A 104 °F (40 °C) - 10 s 1230 A 104 °F (40 °C) - 30 s 950 A 104 °F (40 °C) - 1 min

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

	620 A 104 °F (40 °C) - 3 min 480 A 104 °F (40 °C) - 10 min
Associated fuse rating	315 A aM <= 440 V 400 A BS88 <= 440 V 400 A gG <= 440 V
Average impedance	0.32 mOhm - lth 350 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60158-1 1000 V IEC 60947-4 1000 V BS 775 1500 V VDE 0110 group C
Power dissipation per pole	22 W AC-3 39 W AC-1
Connections - terminals	lugs-ring terminals 1 0.37 in ² (240 mm ²) connector 1 0.37 in ² (240 mm ²) bars 2 32 x 4 mm Power circuit bolted connection
Tightening torque	309.78 lbf.in (35 N.m)
Operating time	40...75 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 104 °F (40 °C)

Complementary

Control circuit voltage limits	Latching 0.85...1.1 Uc Unlatching 0.85...1.1 Uc
Average consumption	1650 VA AC 50/60 Hz latching 9 VA AC 50/60 Hz unlatching

Environment

Protective treatment	TC
Ambient air temperature for operation	5...158 °F (-15...70 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Operating altitude	9842.52 ft (3000 m) without derating
Maximum Height	7.99 in (203 mm)
Maximum Width	7.93 in (201.5 mm)
Maximum Depth	8.39 in (213 mm)
Net Weight	16.31 lb(US) (7.4 kg)

Ordering and shipping details

Category	22331 - CTR,F-LINE,DC,OPEN,NONREV
Discount Schedule	I12
GTIN	00785901548409
Nbr. of units in pkg.	1
Package weight(Lbs)	17.25 lb(US) (7.82 kg)
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.84 in (25 cm)
Package 1 width	9.84 in (25 cm)
Package 1 Length	9.88 in (25.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------