

Product data sheet

Specifications



Electronic VAR compensator/static VAR generator, PowerLogic AccuSine EVC+, 75kvar, 208-480V, UL2 wall mount

EVCP075D5W02

Product availability: Stock - Normally stocked in distribution facility

Price*: 32,496.00 USD

Main

Product name	AccuSine EVC+
Product or Component Type	Electronic VAR compensator

Complementary

Network type	3P
Network configuration	3 or 4 wires
Network rated voltage	208...480 V AC
Input Frequency	50/60 Hz +/- 3 % auto-sensing
Maximum permissible voltage	1.1 x Un
Reactive power rating	75 kvar 380 V AC 50/60 Hz 75 kvar 480 V AC 50/60 Hz 47 kvar 240 V AC 50/60 Hz 41 kvar 208 V AC 50/60 Hz
Operating Mode	Power factor correction Displacement power factor correction Mains current balancing Phase harmonic correction
Installation location	Indoor
enclosure mounting	Wall mounted
Protection Type	Internal by fuse
Disconnect type	Electronic
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Emission tests, class A EN 61000-6-4 Immunity for industrial environments EN 61000-6-2
Accessibility for operation	Front
Location of connection	Bottom

Environment

Enclosure degree of protection	UL type 2
Environmental characteristic	Operating 3C2 IEC 60721-3-3 Operating 3S2 IEC 60721-3-3 Storage 3C3 IEC 60721-3-3 Storage 3S3 IEC 60721-3-3

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Operating altitude	3280.84 ft (1000 m) <= 4800 m 1 % per 100 m <= 4800 m
Ambient air temperature for operation	32...122 °F (0...50 °C) 122...126 °F (50...52 °C) maximum with current derating of 2 % per °C
Relative humidity	0...95 %
PCBA protection	Conformal coated
Standards	UL 508 CSA C22.2 No 14 ISO 9001 IEEE 519-2014 IEC 62477-1 IEC 61439-1
Product Certifications	CE cULus RCM
Ambient Air Temperature for Storage	-4...140 °F (-20...60 °C)
Net Weight	286.6 lb(US) (130 kg)
Height	66.3 in (1685 mm)
Width	21.3 in (540 mm)
Depth	15.08 in (383 mm)
color	White

Ordering and shipping details

Category	US1DE2C00089
Discount Schedule	DE2C
GTIN	3606482047952
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.54 in (42 cm)
Package 1 Width	23.62 in (60 cm)
Package 1 Length	69.49 in (176.5 cm)
Package 1 Weight	368.4 lb(US) (167.1 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[How we assess product sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [Circularity Profile](#)

California Proposition 65 "WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"