

GV4ADM1111

Motor circuit breaker, TeSys GV4, 2 normally open and 2 normally closed contacts, SDx contact module, GV4PEM

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 351.00 USD



Main

Range	TeSys
Device short name	GV4A
Product or component type	Auxiliary contact block
Device application	Signalling
Range compatibility	TeSys GV4 multifunction circuit breaker
Mounting location	Right side
Mounting mode	Clipped
Pole contact composition	2 NO + 2 NC
Connections - terminals	spring terminals 1 0.00...0.00 in ² (0.2...1.5 mm ²)solid spring terminals 1 0.00...0.00 in ² (0.2...2.5 mm ²)flexible without cable end spring terminals 1 0.00...0.00 in ² (0.25...1.5 mm ²)flexible with cable end

Complementary

[Ui] rated insulation voltage	250 V IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Associated fuse rating	5 A gG IEC 60947-5-1
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Rated operational power in VA	400 VA 230...240 V AC-12
Rated operational power in W	50 W 24 V DC-12

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 20, 2020

Ordering and shipping details

Category	22366 -
Discount Schedule	I11
GTIN	03606481166753
Returnability	Yes
Country of origin	US

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.