

# H225R

Safety switch, heavy duty, fusible, 400A, 2 poles,  
125 hp, 50 hp, 240 VAC/250 VDC, NEMA 3R

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 3,884.00 USD



## Main

Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R galvanized steel
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	2
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 1/0...750 kcmil copper or aluminium

## Complementary

Maximum Horse Power Rating	50 hp 250 V DC
Maximum Height	50.31 in (1277.87 mm)
Maximum Depth	10.13 in (257.30 mm)
Maximum Width	27.88 in (708.15 mm)
Tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil

## Ordering and shipping details

Category	00054 - H&HU SW,NEMA3R,400-1200A
----------	----------------------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 3, 2020

Discount Schedule	DE1
GTIN	00785901259237
Nbr. of units in pkg.	1
Package weight(Lbs)	180 lb(US) (81.65 kg)
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	19.81 in (50.31 cm)
Package 1 width	10.98 in (27.879 cm)
Package 1 Length	3.75 in (9.53 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------