

H425AWK

Safety switch, heavy duty, fusible, 400A, 4 poles,
125 hp, 240 VAC/250 VDC, NEMA 12

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 5,640.00 USD



Main

Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12 galvanized steel
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	4
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 1/0...750 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	50 hp 240 V AC 50...60 Hz 3 phase NEC 240.6 125 hp 240 V AC 50...60 Hz 3 phase NEC 430.52 50 hp 250 V DC
Maximum Height	50.25 in (1276.35 mm)
Maximum Depth	9.87 in (250.70 mm)
Maximum Width	33.6 in (853.44 mm)
Tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901333371
Nbr. of units in pkg.	1
Package weight(Lbs)	185 lb(US) (83.91 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------