

H426

Safety switch, heavy duty, fusible, 600A, 4 poles, 200 hp, 240 VAC/250 VDC, NEMA 1

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 8,139.00 USD



Main

Product	Single Throw Safety Switch
Current Rating	600 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 kA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	4
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	250 V DC 240 V AC
Wire Size	AWG 3/0...500 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	75 hp 240 V AC 50...60 Hz 3 phase NEC 240.6 200 hp 240 V AC 50...60 Hz 3 phase NEC 430.52 50 hp 250 V DC
Maximum Height	50.25 in (1276.35 mm)
Maximum Depth	9.87 in (250.70 mm)
Maximum Width	33.6 in (853.44 mm)
Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0...500 kcmil

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 3, 2020

Ordering and shipping details

Category	00053 - H&HU SW,NEMA1,400-1200A
Discount Schedule	DE1
GTIN	00785901452287
Nbr. of units in pkg.	1
Package weight(Lbs)	245 lb(US) (111.13 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------