Product data sheet Characteristics

HDA260405

Circuit breaker, PowerPact H, I-Line, thermal magnetic, 40A, 2 pole, 14 kA, 600 VAC, phase CA

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 1,348.50 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	D

Complementary

Complementary		
Line Rated Current	40 A	
Number of Poles	2P	
Interrupt Rating	25 kA 240 V AC	Ţ.
	18 kA 480 V AC	9
	14 kA 600 V AC	9
	20 kA 250 V DC	<u> </u>
[Ue] rated operational voltage	250 V DC	.0
	600 V AC	o c
Continuous current rating	80 %	<u>-</u>
Mounting mode	I-Line	
Electrical connection	I-Line connection line	- 0
	Lugs load	8
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Phase	CA	<u>.</u>
Magnetic hold current	400 A	
Magnetic tripping current	850 A	<u>:</u>
Maximum Height	9.73 in (247.14 mm)	
Maximum Width	2.94 in (74.68 mm)	
Maximum Depth	4.8 in (121.92 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) AWG 14AWG 3/0)
Environment	
Product certifications	CE UL Listed CSA IEC
Ambient air temperature for operation	104 °F (40 °C)
Ordering and shipping details	
Category	01112 - HD, JD I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901632511
Returnability	Yes
Country of origin	US
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

0 1 1 1	
Contractual	warranty

warranty 18 months
