

HJL36060CU31X

Circuit breaker, PowerPact H, Micrologic 3.2, 60A,
3 pole, 600V, 25kA, 100% rated

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 3,690.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Electronic, standard, Micrologic 3.2, LI
Breaking capacity code	J

Complementary

Line Rated Current	60 A
Number of Poles	3P
Interrupt Rating	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	100 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 14...AWG 3/0 aluminium/copper
Maximum Height	6.4 in (162.56 mm)
Maximum Width	4.12 in (104.65 mm)
Maximum Depth	4.36 in (110.74 mm)
Tightening torque	44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0

Environment

Product certifications	CE CSA UL Listed
------------------------	------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 9, 2020

	CCC IEC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------