Product data sheet Characteristics

HJL36150CU33X

PowerPact H Circuit Breaker, Micrologic 3.2S, 100A, 3P, 600V, 25kA





by Schneider Electric

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 6409.00 USD



Main

IVIAIII		,
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Electronic standard Micrologic 3.2 S LSI	
Breaking capacity code	J	

Complementary

Complementary		
Line Rated Current	150 A	
Poles description	3P	
Breaking capacity	65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC	
System Voltage	600 V AC	
Continuous current rating	100 %	
Mounting mode	Unit mount	
Electrical connection	Lugs load Lugs line	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Height	6.4 in	
Width	4.12 in	
Depth	4.36 in	

Environment

Product certifications	CCC CE CSA IEC UL listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity Schneider- Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	DINP, which is known to the State of California to cause cancer, and
Substance 2	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period 18 months

Product Life Status : Commercialised