Product data sheet Characteristics

HJL36150CU33X

Circuit breaker, PowerPact H, Micrologic 3.2S, 150A, 3 pole, 600V, 25kA, 100% rated

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 9,613.50 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Electronic, standard, Micrologic 3.2 S, LSI
Breaking capacity code	J

Complementary

Main		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip Unit Type	Electronic, standard, Micrologic 3.2 S, LSI	
Breaking capacity code	J	
Complementary		
Line Rated Current	150 A	
Number of Poles	3P	
Interrupt Rating	100 kA 240 V AC	
	65 kA 480 V AC 25 kA 600 V AC	
[Ue] rated operational voltage	600 V AC	
Continuous current rating	100 %	
Mounting mode	Unit mount	
Electrical connection		
Electrical connection	Lugs load Lugs line	
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Maximum Height	6.4 in (162.56 mm)	
Maximum Width	4.12 in (104.65 mm)	
Maximum Depth	4.36 in (110.74 mm)	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) AWG 14AWG 3/0)	
Environment		
Product certifications	IEC	
Froduct certifications	CE	
	CCC	
Price is "List Price" and may be subject to a tra	de discount – check with your local distributor or retailer for actual price.	

Environment

Product certifications	IEC
	CE
	CCC

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





UL	Listed
00	Λ.

Ambient air temperature for operation	104 °F (40 °C)		

Ordering and shipping details

3	
Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

Contractual warranty

Warranty	18 months	

