Product data sheet Characteristics

HJP36050

Circuit breaker, PowerPact H, thermal magnetic, 50A, 3 pole, 600V, 25kA

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 1,949.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	J

Complementary

15 A 2884 15 A 20 A 2		
Main		
Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip Unit Type	Thermal-magnetic	
Breaking capacity code	J	
Complementary		
Line Rated Current	50 A	
Number of Poles	3P	
Interrupt Rating	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC	
[Ue] rated operational voltage	250 V DC 600 V AC	
Continuous current rating	80 %	
Mounting mode	Unit mount	
Electrical connection	Terminal nut line Lugs load	
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Magnetic hold current	400 A	
Magnetic tripping current	850 A	
Maximum Height	6.4 in (162.56 mm)	
Maximum Width	4.12 in (104.65 mm)	
Maximum Depth	4.36 in (110.74 mm)	
Tightening torque	49.5660.18 lbf.in (5.66.8 N.m)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Oct 9, 2020



Environment

Product certifications	CE CSA CCC IEC UL Listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

04445 LICHLIC HUNIT MT DDFAVED/CWITCH
01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
DE2
1
4.13 lb(US) (1.87 kg)
Yes
MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty 18 months

