Product data sheet Characteristics

HU266AWK

Safety switch, heavy duty, non fusible, 600A, 2 poles, 400 hp, 600 VAC/DC, NEMA 12

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 8,112.00 USD



Main

Iviaiii		_ <u></u>
Product	Single Throw Safety Switch	
Current Rating	600 A	a significant and significant
Certifications	UL listed file E2875	
Enclosure Rating	NEMA 3R/12 galvannealed steel	<u> </u>
Factory Installed Neutral	None	
Disconnect Type	Non-fusible disconnect	vilitability
Short Circuit Current Rating	200 kA maximum	aring a
Mounting Type	Surface	in i
Number of Poles	2	<u> </u>
Electrical Connection	Lugs	- Pro-
Duty Rating	Heavy duty	- Des
Voltage Rating	600 V AC/DC	op op
Wire Size	AWG 3/0500 kcmil copper or aluminium	100

Complementary

Maximum Horse Power Rating 200 hp 240 V AC 5060 Hz 3 phase NEC 430.52 400 hp 480 V AC 5060 Hz 3 phase NEC 430.52 50 hp 250 V DC 50 hp 600 V DC Maximum Height 46.25 in (1174.75 mm) Maximum Depth 10.13 in (257.30 mm) Maximum Width 26.25 in (666.75 mm)			
400 hp 480 V AC 5060 Hz 3 phase NEC 430.52 50 hp 250 V DC 50 hp 600 V DC Maximum Height 46.25 in (1174.75 mm) Maximum Depth 10.13 in (257.30 mm) Maximum Width 26.25 in (666.75 mm)	Short-circuit withstand	200 kA	ii.
Maximum Depth 10.13 in (257.30 mm) Maximum Width 26.25 in (666.75 mm)	Maximum Horse Power Rating	400 hp 480 V AC 5060 Hz 3 phase NEC 430.52 50 hp 250 V DC	intended as a si
Maximum Width 26.25 in (666.75 mm)	Maximum Height	46.25 in (1174.75 mm)	
	Maximum Depth	10.13 in (257.30 mm)	C
	Maximum Width	26.25 in (666.75 mm)	
Fightening torque 375 lbf.in (42.37 N.m) AWG 3/0500 kcmil)	Tightening torque	375 lbf.in (42.37 N.m) AWG 3/0500 kcmil)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Life Is On Schneider

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901451310
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	18.21 in (46.251 cm)
Package 1 width	3.99 in (10.13 cm)
Package 1 Length	10.34 in (26.251 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months