Specifications

SQUARE D



Safety switch, heavy duty, non fusible, 600A, 2 pole, 400hp, 600VAC/DC, NEMA 12

HU266AWK

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	2
Current Rating	600 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12 galvannealed steel
Motor power hp	200 hp at 240 V AC 50-60 Hz for 3 phase motors 400 hp at 480 V AC 50-60 Hz for 3 phase motors 50 hp at 250 V DC 50 hp at 600 V DC

Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	2-wire
Wire Size	AWG 3/0500 kcmil copper or aluminium
Tightening torque	375 lbf.in (42.4 N.m) (AWG 3/0500 kcmil)
Depth	10.13 in (257.30 mm)
Width	26.25 in (666.75 mm)
Height	46.25 in (1174.75 mm)
Net Weight	170.0 lb(US) (77.1 kg)

Environment

Certifications

UL listed file E2875

Ordering and shipping details

Category	US10DE100155
Discount Schedule	0DE1
GTIN	785901451310

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.21 in (46.251 cm)
Package 1 Width	3.99 in (10.13 cm)
Package 1 Length	10.34 in (26.251 cm)
Package 1 Weight	170.0008 lb(US) (77.111 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green Premium[™] label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

How we assess product sustainability >



Transparency

Well-being performance

Reach Free Of Svhc

	Mercury Free	
	Rohs Exemption Information	Yes
	Halogen Content Performance	Halogen free plastic parts product
	Pvc Free	Yes
Eu F	Rohs Directive	Compliant
Eu f	Rohs Directive	Compliant EU RoHS Declaration
	Rohs Directive na Rohs Regulation	
		EU RoHS Declaration
Chir		EU RoHS Declaration China RoHS declaration