Product data sheet Characteristics

JDA36200

Circuit breaker, PowerPact J, I-Line, thermal magnetic, 200A, 3 pole, 14 kA, 600 VAC, phase ABC

Product availability: Stock - Normally stocked in distribution facility





Price*: 2,867.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	D

Complementary

Complementary		
Line Rated Current	200 A	
Number of poles	3	ζ
Poles description	3P	Ţ
Breaking capacity	25 kA 240 V AC 18 kA 480 V AC 14 kA 600 V AC 20 kA 250 V DC	. i
[Ue] rated operational voltage	600 V AC 250 V DC	
Continuous current rating	80 %	190
Mounting mode	I-Line	0
Electrical connection	I-Line connection line Lugs load	iri budad
AWG gauge	AWG 3/0350 kcmil aluminium/copper	<u>.</u>
Phase connection	ABC	.0
Magnetic hold current	1000 A	
Magnetic tripping current	2000 A	
Maximum Height	11.48 in (291.59 mm)	
Maximum Width	4.48 in (113.79 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Maximum Depth	5.87 in (149.10 mm)	
Net Weight	5.29 lb(US) (2.4 kg)	
Environment		
Product certifications	CE	
	IEC	
	CSA	
	UL Listed	

Ordering and shipping details

Ambient air temperature for operation

CCC

104 °F (40 °C)

5	
Category	01112 - HD, JD I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901539766
Returnability	Yes
Country of origin	MX

Packing Units

	Unit Type of Package 1	PCE			
--	------------------------	-----	--	--	--

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months		