Product data sheet Characteristics

JDA36250

Circuit breaker, PowerPact J, I-Line, thermal magnetic, 250A, 3 pole, 14 kA, 600 VAC, phase ABC

Product availability: Stock - Normally stocked in distribution facility





Price*: 3,936.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	D

Complementary

Complementary		
Line Rated Current	250 A	
Number of poles	3	7
Poles description	3P	Ţ.
Breaking capacity	25 kA 240 V AC 18 kA 480 V AC 14 kA 600 V AC 20 kA 250 V DC	. i
[Ue] rated operational voltage	600 V AC 250 V DC	
Continuous current rating	80 %	190
Mounting mode	I-Line	0
Electrical connection	I-Line connection line Lugs load	iri budad
AWG gauge	AWG 3/0350 kcmil aluminium/copper	<u>.</u>
Phase connection	ABC	. <u>.</u> . <u>.</u>
Magnetic hold current	1250 A	
Magnetic tripping current	2500 A	
Maximum Height	11.48 in (291.59 mm)	
Maximum Width	4.48 in (113.79 mm)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Maximum Depth	5.87 in (149.10 mm)	
Environment		
Product certifications	CE IEC UL Listed CSA CCC	
Ambient air temperature for operation	104 °F (40 °C)	
Ordering and shipping details		
Category	01112 - HD, JD I-LINE BREAKER/SWITCH	
Discount Schedule	DE2	
GTIN	00785901834175	
Returnability	Yes	
Country of origin	MX	
Packing Units		
Unit Type of Package 1	PCE	
Offer Sustainability		
Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
China RoHS Regulation	Product out of China RoHS scope. Substance declaration for your information.	
China RoHS Regulation Environmental Disclosure	Product out of China RoHS scope. Substance declaration for your information. Product Environmental Profile	

Con	tractua	warranty

	Warranty	18 months
--	----------	-----------



