



Price* : 3,120.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Electronic, standard, Micrologic 3.2, LI
Breaking capacity code	D

Complementary

Line Rated Current	250 A
Number of poles	3
Poles description	3P
Breaking capacity	25 kA 240 V AC 18 kA 480 V AC 14 kA 600 V AC
[Ue] rated operational voltage	600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...350 kcmil aluminium/copper
Phase connection	ABC
Maximum Height	11.48 in (291.59 mm)
Maximum Width	4.48 in (113.79 mm)
Maximum Depth	5.87 in (149.10 mm)
Tightening torque	230.12 lbf.in (26 N.m) 0.15...0.29 in ² (95...185 mm ²) AWG 3/0...350 kcmil)

Environment

Product certifications	UL Listed
------------------------	-----------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 11, 2020

CCC
CE
IEC
CSA

Ambient air temperature for operation	122 °F (50 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	01104-H/J ELEC TRIP I-LINE BREAKER / SW
Discount Schedule	DE2
GTIN	00785901127222
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
