Product data sheet Characteristics

JJF36200

PowerPact J-Frame breaker, thermal-magnetic, 200 A, 3P, 25 kA at 600 VAC

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 8,148.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	J

Complementary

Line Rated Current Number of poles 3 Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 250 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	9		
Product or component type Range of product PowerPact J Trip unit technology Preaking capacity code Thermal-magnetic Breaking capacity code Complementary Line Rated Current Number of poles 3 Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 680 V AC 20 kA 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection line Busbar connection load Magnetic tripping current 1000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Trightening torque Complementary Trip unit technology Thermal-magnetic PowerPact J Thermal-magnetic Range of product 1000 A Thermal-magnetic 1000 A 100	10.0		
Product or component type Range of product PowerPact J Trip unit technology Preaking capacity code Thermal-magnetic Breaking capacity code Complementary Line Rated Current Number of poles 3 Poles description Breaking capacity 100 KA 240 V AC 65 KA 480 V AC 25 KA 600 V AC 20 KA 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque Complementary Thermal-magnetic Torquit bewere A Thermal-magnetic The			
Product or component type Range of product PowerPact J Trip unit technology Preaking capacity code Thermal-magnetic Breaking capacity code Complementary Line Rated Current Number of poles 3 Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 680 V AC 20 kA 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection line Busbar connection load Magnetic tripping current 1000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Trightening torque Complementary Trip unit technology Thermal-magnetic PowerPact J Thermal-magnetic Range of product 1000 A Thermal-magnetic 1000 A 100			
Product or component type Range of product PowerPact J Trip unit technology Preaking capacity code Thermal-magnetic Breaking capacity code Complementary Line Rated Current Number of poles 3 Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic tripping current 1000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque Complementary Trip unit technology Thermal-magnetic June PowerPact J Thermal-magnetic June Pact June Pact June Pact J Thermal-magnetic June Pact June Pact J Thermal-magnetic June Pact June Pact J Thermal-magnetic June Pact June Pact J Th			
Range of product PowerPact J Trip unit technology Thermal-magnetic Breaking capacity code J Complementary Line Rated Current 200 A Number of poles 3 Poles description 3P Breaking capacity 200 A Solve A 480 V AC 25 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 25 kA 500 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 200. A Marina Marina A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A 1 A	Main		
Trip unit technology Breaking capacity code Complementary Line Rated Current 200 A Number of poles 3 Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 600 V AC 25 kA 600 V AC 25 kA 600 V AC 26 kOV DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque Thermal-magnetic John All Simular Mayor Ac 200 A John John	Product or component type	Circuit breaker	
Breaking capacity code Complementary Line Rated Current 200 A Number of poles 3 Poles description 3P Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 2000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 2001 A	Range of product	PowerPact J	
Complementary Line Rated Current 200 A Number of poles 3 Poles description 3P Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 25 kA 600 V AC 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Trip unit technology	Thermal-magnetic	
Line Rated Current 200 A Number of poles 3 Poles description 3P Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 25 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Breaking capacity code	J	
Number of poles 3 Poles description 3P Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Line Rated Current 200 A Number of poles 3 Poles description 3P Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 25 kA 600 V AC 250 kD DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Complementary		
Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic ripping current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)		200 A	
Poles description Breaking capacity 100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Number of poles	3	
65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC [Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)		3P	
25 kA 600 V AC 20 kA 250 V DC		100 kA 240 V AC	
[Ue] rated operational voltage 600 V AC 250 V DC Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Continuous current rating 80 % Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	[Ue] rated operational voltage	600 V AC	
Mounting mode Unit mount Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Electrical connection Busbar connection line Busbar connection load Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Continuous current rating	80 %	
Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Mounting mode	Unit mount	
Magnetic hold current 1000 A Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	Electrical connection		
Magnetic tripping current 2000 A Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	N. C. L. I.		
Maximum Height 7.52 in (191.01 mm) Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Maximum Width 4.12 in (104.65 mm) Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Maximum Depth 5 in (127.00 mm) Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)			
Tightening torque 230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	924-146 MAGDIE 1810 (2) MACHIS 1 (1) - 30 (3) 1/100 QUESTION		
	/A		
* Drice is "List Drice" and may be subject to a trade discount, wheels with your local distributes as a trade discount.	Tightening torque	230.12 lbf.in (26 N.m) 0.150.29 in² (95185 mm²) AWG 3/0350 kcmil)	
* Drice is "list Drice" and may be subject to a trade discount. shoot with your level distributer as a trade discount.			
* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	* Price is "List Price" and may be subject to a tra	de discount – check with your local distributor or retailer for actual price.	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Oct 21, 2020



Environment

Product certifications	IEC CCC CSA UL Listed CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

The state of the s	
Warranty	18 months