Specifications



# Fuse disconnector, TeSys DF, 1P, 600V, 30A, 10 x 38mm, Add on for LS1D32

LA8D324

Product availability: Stock - Normally stocked in distribution facility

## Price\*: 34.80 USD

#### Main

| Range                     | TeSys             |
|---------------------------|-------------------|
| Product or Component Type | Fuse-disconnector |
| Device short name         | LA8D              |
| Poles description         | 1P                |

## Complementary

| oompicinentai y                |  |
|--------------------------------|--|
| Mounting Support               | Rail   |
| Mounting position              | Vertical +/- 23°)  |
| Control Type                   | Toggle   |
| [Ue] rated operational voltage | 600 V  |
| [le] rated operational current | 30 A   |
| Local signalling               | Blown fuse indication  |
| Fuse size                      | 10 x 38 mm   |
| Fuse type                      | AM<br>GG   |
| Associated fuse rating         | 30 A aM<br>30 A gG   |
| Connections - terminals        | screw clamp terminals 2 0.0020.009 in <sup>2</sup> (16 mm <sup>2</sup> )solid<br>screw clamp terminals 2 0.0020.009 in <sup>2</sup> (16 mm <sup>2</sup> )flexible without cable end<br>screw clamp terminals 2 0.0020.006 in <sup>2</sup> (14 mm <sup>2</sup> )flexible with cable end |
| Tightening torque              | 15.05 lbf.in (1.7 N.m) screw clamp terminals   |
|                                |  |

## Environment

| Standards                             | IEC 60947-2<br>IEC 60947-1<br>IEC 60947-4-1 |
|---------------------------------------|---|
| Product Certifications                | BV  |
| Protective treatment                  | тн  |
| Ambient air temperature for operation | -58158 °F (-5070 °C) operation              |
| Height                                | 3.5 in (89 mm)                              |
| Width                                 | 1.8 in (45 mm)                              |
| Depth                                 | 2.7 in (68.3 mm)                            |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

## Ordering and shipping details

| Category          | US10I1222341   |
|-------------------|----------------|
| Discount Schedule | 0112           |
| GTIN              | 00785901046950 |
| Returnability     | Yes            |
| Country of origin | MX             |

## **Packing Units**

| J                            |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 0.79 in (2.0 cm)        |
| Package 1 Width              | 2.36 in (6.0 cm)        |
| Package 1 Length             | 3.54 in (9.0 cm)        |
| Package 1 Weight             | 2.3 oz (64.0 g)         |
| Unit Type of Package 2       | \$01                    |
| Number of Units in Package 2 | 20                      |
| Package 2 Height             | 5.91 in (15.0 cm)       |
| Package 2 Width              | 5.91 in (15.0 cm)       |
| Package 2 Length             | 15.75 in (40.0 cm)      |
| Package 2 Weight             | 3.455 lb(US) (1.567 kg) |
| Unit Type of Package 3       | P06                     |
| Number of Units in Package 3 | 560                     |
| Package 3 Height             | 30.31 in (77.0 cm)      |
| Package 3 Width              | 31.50 in (80.0 cm)      |
| Package 3 Length             | 23.62 in (60.0 cm)      |
| Package 3 Weight             | 96.52 lb(US) (43.78 kg) |
|                              |                         |

## **Contractual warranty**

Warranty

18 months

## **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

How we assess product sustainability >

### Well-being performance

| Reach Free Of Svhc         |  |
|----------------------------|--|
| V Toxic Heavy Metal Free   |  |
| Mercury Free               |  |
| Rohs Exemption Information | Yes  |
| Reach Regulation           | REACh Declaration  |
| Eu Rohs Directive          | Compliant<br>EU RoHS Declaration   |
| China Rohs Regulation      | China RoHS declaration   |
| Weee                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |