

LAL3640031M

LAL MOTOR CIRCUIT PROTECTOR, 600VAC/250VDC, 400A, 3P

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 4,619.00 USD



Main

Product or component type	Motor Circuit Protector
Trip Unit Type	Thermal-magnetic

Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	42 kA 240 V AC 30 kA 480 V AC 22 kA 600 V AC 10 kA 125 V DC 10 kA 250 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	1125 A
Magnetic tripping current	2250 A
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)
Tightening torque	115.06 lbf.in (13 N.m) 0.07...0.47 in ² (42...304 mm ²) AWG 1...600 kcmil) 115.06 lbf.in (13 N.m) 0.07...0.20 in ² (42...127 mm ²) AWG 1...250 kcmil)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 12, 2020

Environment

Product certifications	IEC UL Listed CSA
------------------------	-------------------------

Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901358381
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------