Product data sheet Characteristics

LAL36400WB FA/LA MOLDED CASE CIRCUIT BREAKER 600V, 400A, 3P,

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 7,297.50 USD



Main

Product or component type	Circuit breaker
Trip Unit Type	Thermal-magnetic
Options	Mechanical interlock

Complementary

Complementary		
Line Rated Current	400 A	
Number of Poles	3P	
Interrupt Rating	42 kA 240 V AC 30 kA 480 V AC 22 kA 600 V AC 10 kA 125 V DC 10 kA 250 V DC	
[Ue] rated operational voltage	600 V AC 250 V DC	
Mounting mode	Unit mount	
Electrical connection	Lugs load Lugs line	9
Wire Gauge	AWG 1600 kcmil aluminium/copper)1 AWG 1250 kcmil aluminium/copper)2	
Terminal Type	AL400LA	
Magnetic hold current	2000 A	
Magnetic tripping current	4000 A	-0
Maximum Height	11 in (279.40 mm)	
Maximum Width	6 in (152.40 mm)	
Maximum Depth	5.84 in (148.34 mm)	
Tightening torque	115.06 lbf.in (13 N.m) 0.070.47 in² (42304 mm²) AWG 1600 kcmil) 115.06 lbf.in (13 N.m) 0.070.20 in² (42127 mm²) AWG 1250 kcmil)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Environment

Product certifications	UL Listed
	IEC
	CSA

Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901397472
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

,		
Warranty	18 months	

