

LJA34250WU31X

Circuit breaker, PowerPact L, I-Line, Micrologic 3.3, 250A, 80% rated, 3 pole, 65 kA, 480 VAC, phase ABC



Price* : 10,299.00 USD



Main

Range of product	PowerPact L
Product or component type	Circuit breaker
Trip Unit Type	Electronic, standard, Micrologic 3.3 W, LI
Interrupt Code	J

Complementary

Line Rated Current	250 A
Number of Poles	3P
Interrupt Rating	100 kA 240 V AC 65 kA 480 V AC 65 kA 240 V AC
Voltage Rating	480 V AC
Continuous current rating	80 %
Protection technology	Current limiter
Mounting mode	I-Line
Electrical connection	I-Line connection line Terminal nut load
Wire Size	AWG 2...500 kcmil aluminium)1 AWG 2...600 kcmil copper)1
Terminal Type	AL400L61K3
I-Line Phase Connection	ABC
Maximum Height	11.3 in (287.02 mm)
Maximum Width	5.5 in (139.70 mm)
Maximum Depth	6.61 in (167.89 mm)
Tightening torque	442.54 lbf.in (50 N.m) 0.05...0.37 in ² (35...240 mm ²) AWG 2...500 kcmil) 442.54 lbf.in (50 N.m) 0.05...0.47 in ² (35...300 mm ²) AWG 2...600 kcmil)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 11, 2020

Environment

Product certifications	CSA 22-2 CCC IEC CE UL 489 NMX NEMA
------------------------	---

Ordering and shipping details

Category	01118-L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901979982
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------