Product data sheet Characteristics

LLA36000S60X AUTOMATIC MOLDED CASE SWITCH 600V 600A

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 8,520.00 USD



Main

Product or component type	Automatic switch	- -
Range of product	PowerPact L	9
Trip unit technology	Magnetic	**************************************

Complementary

Complementary		ō >
Line Rated Current	600 A	tabilit
[Ue] rated operational voltage	600 V AC	o Sui
Mounting mode	I-Line	
Poles description	3P	deter
Short-circuit withstand	125 kA 240 V UL 489 100 kA 480 V UL 489 50 kA 600 V UL 489	not to be used for determining suitability
Breaking capacity code	L	or
Electrical connection	Lugs load I-Line connection line	substitute for and is
AWG gauge	AWG 3/0500 kcmil aluminium/copper)2	
Terminal identifier	AL600LF52K3	
Magnetic tripping current	6600 A	ກ ໝ <u>ໜ</u>
Maximum Height	13 in (330.20 mm)	
Maximum Width	6 in (152.40 mm)	s not intended
Maximum Depth	4.75 in (120.65 mm)	s not
Tightening torque	442.54 lbf.in (50 N.m) 0.150.37 in² (95240 mm²) AWG 3/0500 kcmil)	tation is

Environment

Product certifications	CSA
	NMX

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





CCC UL Listed IEC CE

Ordering and shipping details

0 11 0	
Category	01118 - L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901146254
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

Contractual warranty

	,	
Warranty	18 months	