



Price* : 110.00 USD



Main

| | |
|--------------------------------|---|
| Range of product | TeSys K |
| Range | TeSys |
| Product or component type | Contactor |
| Device short name | LP4K |
| Contactor application | Resistive load |
| Utilisation category | AC-1 |
| Poles description | 4P |
| Pole contact composition | 4 NO |
| [Ue] rated operational voltage | 20 A 122 °F (50 °C)) <= 440 V AC AC-1 power circuit 16 A 158 °F (70 °C)) 690 V AC AC-1 power circuit |

Complementary

| | |
|--------------------------------|--|
| Coil technology | Built-in bidirectional peak limiting diode suppressor |
| Control circuit voltage limits | Operational 0.7...1.30 U _c 122 °F (50 °C)) Drop-out 0.1...0.7 U _c 122 °F (50 °C)) |
| Standards | Power circuit 600 V UL 508 Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA C22.2 No 14 |
| Standards | 110 A AC power circuit NF C 63-110 110 A AC power circuit IEC 60947 |
| Electrical circuit type | 25 A gG <= 440 V power circuit 25 A aM power circuit |
| Electrical circuit type | 3 mOhm - Ith 20 A 50 Hz power circuit |
| Overtoltage category | III |
| Mounting support | Printed circuit boards |
| Flame retardance | V1 UL 94 Requirement 2 NF F 16-101 |

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Requirement 2 NF F 16-102

| | |
|---|--|
| [Ue] rated operational voltage | Power circuit 690 V AC 50/60 Hz |
| Maximum ambient air temperature for operation | 20 A 122 °F (50 °C) power circuit |
| [Ue] rated operational voltage | 110 A 415 V IEC 60947 110 A 440 V IEC 60947 80 A 500 V IEC 60947 110 A 220...230 V IEC 60947 110 A 380...400 V IEC 60947 70 A 660...690 V IEC 60947 |
| Operating time | 30...40 ms coil energisation and NO closing 10 ms coil de-energisation and NO opening |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 |
| Maximum operating rate | 3600 cyc/h |

Environment

| | |
|------------------------|--------------------------------------|
| Product certifications | UL CSA |
| Operating altitude | 6561.68 ft (2000 m) without derating |

Ordering and shipping details

| | |
|-----------------------|-----------------------------------|
| Category | 22321 - CTR,K-LINE,DC,OPEN,NONREV |
| Discount Schedule | I12 |
| GTIN | 03389110498714 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.58 lb(US) (0.26 kg) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 width | 2.44 in (6.2 cm) |
| Package 1 Length | 2.60 in (6.6 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
