

Product availability : Stock - Normally stocked in distribution facility



Price* : 375.00 USD



Main

Range	TeSys
Product name	TeSys U
Device short name	LUB
Product or component type	Non reversing power base
Device application	Motor control Motor protection
Poles description	3P
Suitability for isolation	Yes
[Ue] rated operational voltage	690 V AC power circuit
Network frequency	40...60 Hz
[Ith] conventional free air thermal current	32 A
[Ie] rated operational current	32 A <= 440 V 23 A 500 V 21 A 690 V
Utilisation category	AC-44 AC-41 AC-43
[Ics] rated service breaking capacity	50 kA 230 V 50 kA 440 V 10 kA 500 V 4 kA 690 V
Auxiliary contact composition	1 NO + 1 NC
Auxiliary contacts type	Linked contacts 1 NO + 1 NC) IEC 60947-4-1 Mirror contact 1 NC) IEC 60947-1
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC 48...72 V AC 50/60 Hz 48...72 V DC 110...240 V AC 50/60 Hz 110...220 V DC

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 2, 2020

Complementary

Typical current consumption	<p>200 mA 24 V DC I maximum while closing with LUCM</p> <p>220 mA 24 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>220 mA 24 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>25 mA 110...220 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>25 mA 110...240 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 110...220 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 110...240 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 48...72 V AC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>280 mA 48...72 V DC I maximum while closing with LUCA, LUCB, LUCC, LUCD</p> <p>45 mA 48...72 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>45 mA 48...72 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>75 mA 24 V DC I rms sealed with LUCM</p> <p>80 mA 24 V DC I rms sealed with LUCA, LUCB, LUCC, LUCD</p> <p>90 mA 24 V AC I rms sealed with LUCA, LUCB, LUCC, LUCD</p>
Heat dissipation	<p>3 W control circuit with LUCA, LUCB, LUCC, LUCD</p> <p>1.8 W control circuit with LUCM</p>
Safety reliability level	<p>B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1</p> <p>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1</p>
Operating time	<p>35 ms opening with LUCA, LUCB, LUCC, LUCD, LUCM control circuit</p> <p>50 ms >= 72 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>60 ms 48 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>70 ms 24 V closing with LUCA, LUCB, LUCC, LUCD control circuit</p> <p>65 ms closing with LUCM control circuit</p>
Mechanical durability	15 Mcycles
Maximum operating rate	3600 cyc/h
Product certifications	<p>CE</p> <p>UL</p> <p>CSA</p> <p>CCC</p> <p>EAC</p> <p>ASEFA</p> <p>ATEX</p> <p>Marine</p>
Standards	<p>EN 60947-6-2</p> <p>IEC 60947-6-2</p> <p>UL 60947-4-1, with phase barrier</p> <p>CSA C22.2 No 60947-4-1, with phase barrier</p>
[Ui] rated insulation voltage	<p>690 V IEC 60947-6-2 3)</p> <p>600 V UL 60947-4-1</p> <p>600 V CSA C22.2 No 60947-4-1</p>
[Uimp] rated impulse withstand voltage	6 kVIEC 60947-6-2
Safe separation of circuit	<p>400 V SELV between the control and auxiliary circuits IEC 60947-1 appendix N</p> <p>400 V SELV between the control or auxiliary circuit and the main circuit IEC 60947-1 appendix N</p>
Fixing mode	<p>Clipped DIN rail)</p> <p>Screw-fixed plate)</p>
Connections - terminals	<p>Power circuit screw clamp terminals 1 0.00...0.02 in² (1...10 mm²) rigid</p> <p>Power circuit screw clamp terminals 1 0.00...0.01 in² (1...6 mm²) flexible with cable end</p> <p>Power circuit screw clamp terminals 1 0.00...0.02 in² (2.5...10 mm²) flexible without cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1...6 mm²) flexible with cable end</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1...6 mm²) rigid</p> <p>Power circuit screw clamp terminals 2 0.00...0.01 in² (1.5...6 mm²) flexible without cable end</p> <p>Control circuit without connection</p>
Tightening torque	<p>Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) flat 0.20 in (5 mm)</p> <p>Control circuit 7.08...10.62 lbf.in (0.8...1.2 N.m) Philips no 1 0.20 in (5 mm)</p> <p>Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) flat 0.24 in (6 mm)</p> <p>Power circuit 16.82...22.13 lbf.in (1.9...2.5 N.m) Philips No 2 0.24 in (6 mm)</p>
Maximum Width	1.77 in (45 mm)
Maximum Height	6.06 in (154 mm)
Maximum Depth	4.96 in (126 mm)
Net Weight	1.91 lb(US) (0.865 kg)
Compatibility code	LUB

Environment

IP degree of protection	IP20 IEC 60947-1 front panel and wired terminals) IP20 IEC 60947-1 other faces) IP40 IEC 60947-1 front panel outside connection zone)
Protective treatment	TH IEC 60068
Ambient air temperature for operation	-13...140 °F (-25...60 °C) with LUCM -13...158 °F (-25...70 °C) with LUCA, LUCB, LUCC, LUCD
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Fire resistance	1760 °F (960 °C) parts supporting live components IEC 60695-2-12 1202 °F (650 °C) IEC 60695-2-12
Operating altitude	6561.68 ft (2000 m)
Shock resistance	10 gn power poles open IEC 60068-2-27 15 gn power poles closed IEC 60068-2-27
Vibration resistance	2 gn 5...300 Hz) power poles open IEC 60068-2-27 4 gn 5...300 Hz) power poles closed IEC 60068-2-27
Resistance to electrostatic discharge	8 kV 3 in open air IEC 61000-4-2 8 kV 4 on contact IEC 61000-4-2
Resistance to radiated fields	9.14 V/m (10 V/m) 3 IEC 61000-4-3
Resistance to fast transients	2 kV 3 serial link IEC 61000-4-4 4 kV 4 all circuits except for serial link IEC 61000-4-4
Non-dissipating shock wave	1 kV serial mode 24...240 V AC IEC 60947-6-2 1 kV serial mode 48...220 V DC IEC 60947-6-2 2 kV common mode 24...240 V AC IEC 60947-6-2 2 kV common mode 48...220 V DC IEC 60947-6-2
Immunity to radioelectric fields	10 V IEC 61000-4-6
Immunity to microbreaks	3 ms control circuit
Immunity to voltage dips	70 % / 500 ms IEC 61000-4-11

Ordering and shipping details

Category	22396 - TESYS U - SELF PRCTD STARTER (LUB)
Discount Schedule	I11
GTIN	00785901221821
Nbr. of units in pkg.	1
Package weight(Lbs)	1.82 lb(US) (0.83 kg)
Returnability	Yes
Country of origin	FR

Packing Units

Package 1 Height	1.720 dm
Package 1 width	0.570 dm
Package 1 Length	1.450 dm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
