Product data sheet Characteristics

LUFN02

auxiliary contacts LUF - 2NC

Product availability: Stock - Normally stocked in distribution facility



Price*: 34.50 USD



Main

Range	TeSys
Device short name	LUFN
Product or component type	Auxiliary contact

Complementary

		-
Auxiliary contact composition	2 NC	
[Ue] rated operational voltage	<= 250 V AC <= 250 V DC	suitability
[Ui] rated insulation voltage	250 V CSA 250 V IEC 60947-5-1 250 V UL	letermining
[lth] conventional free air thermal current	5 A	o Joj pesn
Minimum switching voltage	17 V	9
Minimum switching current	5 mA	
Net Weight	0.11 lb(US) (0.05 kg)	is pure

Ordering and shipping details

		±
Category	22399 - TESYS U, ACCESSORIES	ā
Discount Schedule	l11	
GTIN	00785901412441	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.12 lb(US) (0.05 kg)	<u>.</u>
Returnability	Yes	- in
Country of origin	FR	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.34 in (3.4 cm)
Package 1 width	1.89 in (4.8 cm)
Package 1 Length	3.74 in (9.5 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Weight	3.61 lb(US) (1.638 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------