Product data sheet Characteristics

LUFN20

TeSys U, auxiliary contact module, 2 NO

Product availability: Stock - Normally stocked in distribution facility



Price*: 34.50 USD



Main

Range	TeSys
Device short name	LUFN
Product or component type	Auxiliary contact

Complementary

Main		
Range	TeSys	
Device short name	LUFN	
Product or component type	Auxiliary contact	
Complementary		
Auxiliary contact composition	2 NO	
[Ue] rated operational voltage	<= 250 V AC <= 250 V DC	
[Ui] rated insulation voltage	250 V CSA 250 V IEC 60947-5-1 250 V UL	
[Ith] conventional free air thermal current	5 A	
Minimum switching voltage	17 V	
Minimum switching current	5 mA	
Net Weight	0.11 lb(US) (0.05 kg)	
Ordering and shipping details		
Category	22399 - TESYS U, ACCESSORIES	
Discount Schedule	I11	
GTIN	00785901510017	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.12 lb(US) (0.05 kg)	
Returnability	Yes	
	FR	
Country of origin		
Country of origin		

Ordering and shipping details

		2
Category	22399 - TESYS U, ACCESSORIES	Č
Discount Schedule	l11	7
GTIN	00785901510017	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.12 lb(US) (0.05 kg)	
Returnability	Yes	
Country of origin	FR	<u> </u>
		i

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	1.42 in (3.6 cm)	
Package 1 width	1.81 in (4.6 cm)	
Package 1 Length	3.94 in (10 cm)	

Offer Sustainability

Green Premium product
Yes
Compliant EU RoHS Declaration
Yes
Yes
Yes
China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

|--|