

Product data sheet

Specifications



Service interface kit, Pact series circuit breakers

LV485500

Product availability: Stock - Normally stocked in distribution facility

Price*: 15,000.00 USD

Main

Product or Component Type	Testing kit
accessory / separate part category	Maintenance accessory
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW EasyPact EasyPact MVS ComPact ComPact NS630b...1600 ComPact ComPact NS1600b...3200
Provided equipment	1 Power supply 1 USB cable 3 test cables
[Ue] rated operational voltage	115/230 V AC +/- 10 % 47...63 Hz
Trip time measurement	0...7500 s +/- 0.1 %

Complementary

[Uimp] rated impulse withstand voltage	12 kV
IP degree of protection	IP20
Height	4.2 in (106 mm)
Width	17.8 in (451 mm)
Depth	14.09 in (358 mm)
Net Weight	6.2 lb(US) (2.8 kg)
Product Certifications	CE UL
Standards	IEC 61010-1 IEC 61010-2-030 UL 61010-1 CSA C22.2 No 61010-1 EN 60068-2-32

Environment

Overvoltage category	II
Electromagnetic compatibility	Conducted RF disturbances EN 55011 Emission tests EN 55032 Immunity for industrial environments IEC 61000-6-2 Emission standard for industrial environments IEC 61000-6-4 Limits for harmonic current emissions IEC 61000-3-2 Limitation of voltage changes, voltage fluctuations and flicker in low-voltage IEC 61000-3-3
Ambient Air Temperature for Operation	14...131 °F (-10...55 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Relative humidity	5...95 % 131 °F (55 °C)
-------------------	-------------------------

Ordering and shipping details

Category	US1DE2F01290
----------	--------------

Discount Schedule	DE2F
-------------------	------

GTIN	3606481907011
------	---------------

Returnability	Yes
---------------	-----

Country of origin	US
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	4.53 in (11.5 cm)
------------------	-------------------

Package 1 Width	14.96 in (38.0 cm)
-----------------	--------------------

Package 1 Length	18.50 in (47.0 cm)
------------------	--------------------

Package 1 Weight	10.27 lb(US) (4.66 kg)
------------------	------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[How we assess product sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 "WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov"

Scip Number 02103669-1f7b-405d-b4c0-2d7df252a0cd