



Price* : 60.00 USD



Main

Range of product	Multi 9
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
Line Rated Current	3 A 415 V AC - 50/60 Hz 6 A <= 240 V AC - 50/60 Hz 6 A 24 V DC 2 A 48 V DC 1.5 A 60 V DC 1 A 130 V DC
[Uc] control circuit voltage	240...415 V AC 50/60 Hz 24...130 V DC
9 mm pitches	1

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP Multi 9 C60H-DC
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed
Mounting support	DIN rail
Maximum Height	3.35 in (85 mm)
Maximum Width	0.35 in (9 mm)
Maximum Depth	2.89 in (73.5 mm)
Net Weight	1.06 oz (30 g)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Connections - terminals	Clamp terminal bottom) 1 0.00 in ² (2.5 mm ²) AWG 14) - rigid Clamp terminal bottom) 2 0.00 in ² (1.5 mm ²) AWG 16) - rigid
Wire stripping length	0.35 in (9 mm) bottom
Tightening torque	8.85 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	CSA PCT UL UR CCC
Ambient air temperature for operation	-13...122 °F (-25...50 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	00948 - M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	00785901760634
Nbr. of units in pkg.	1
Package weight(Lbs)	0.09 lb(US) (0.04 kg)
Returnability	Yes
Country of origin	BE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.83 in (2.1 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.70 in (9.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	18.55 oz (526 g)
Package 2 Height	3.94 in (10 cm)
Package 2 width	3.54 in (9 cm)
Package 2 Length	10.63 in (27 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	11.25 lb(US) (5.101 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
