Product data sheet Characteristics

M9A26929

Multi 9 - double OC or fault contact - 1 OF+SD/OF - 240/415 V AC - 24/130 V DC

Product availability: Stock - Normally stocked in distribution facility



Price*: 80.00 USD



Main

Man		
Range of product	Multi 9	1
Product or component type	Double OC or fault contact	
Device short name	SD + OF	
Signal contacts composition	2 C/O	: :
Line Rated Current	3 A 415 V AC - 50/60 Hz 6 A <= 240 V AC - 50/60 Hz	
[Uc] control circuit voltage	240415 V AC 50/60 Hz 24130 V DC	
9 mm pitches	1	

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP GFP Multi 9 C60H-DC C60H-DC	
[Ui] rated insulation voltage	500 V	9
[Uimp] rated impulse withstand voltage	4 kV	-
Mounting mode	Fixed	C
Mounting support	DIN rail	7
Maximum Height	3.54 in (90 mm)	
Maximum Width	0.35 in (9 mm)	
Maximum Depth	2.89 in (73.5 mm)	
Net Weight	0.08 lb(US) (0.038 kg)	
Connections - terminals	Clamp terminal bottom) 1 0.00 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) 2 0.00 in² (1.5 mm²) AWG 16) - rigid	
Wire stripping length	0.35 in (9 mm) bottom	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.





Tightening torque	8.85 lbf.in (1 N.m) bottom	
-------------------	----------------------------	--

Environment

A CONTRACT OF THE PROPERTY OF	
Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	UR UL CCC PCT CSA
Ambient air temperature for operation	-13122 °F (-2550 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)

Ordering and shipping details

0 11 0	
Category	00948 - M9 GEN 2 CB UL1077 / IEC
Discount Schedule	DE2
GTIN	00785901760658
Nbr. of units in pkg.	1
Package weight(Lbs)	0.1 lb(US) (0.05 kg)
Returnability	Yes
Country of origin	BE

Packing Units

r acking office	
Unit Type of Package 1	PCE
Package 1 Height	0.87 in (2.2 cm)
Package 1 width	3.07 in (7.8 cm)
Package 1 Length	3.70 in (9.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	22.05 oz (625 g)
Package 2 Height	3.94 in (10 cm)
Package 2 width	3.54 in (9 cm)
Package 2 Length	10.63 in (27 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	13.24 lb(US) (6.004 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)
-	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	