



## Main

Range	PowerLogic
Product or component type	Current transducer
Accessory / separate part category	Measurement accessory
Range compatibility	Acti 9 iEM3000 iEM3555 Acti 9 iEM3000 iEM3565 PowerLogic EM4200 EM4235 PowerLogic EM4200 EM4236 PowerLogic EM3500 EM3502A PowerLogic EM3500 EM3550A PowerLogic EM3500 EM3555A PowerLogic EM3500 EM3560A PowerLogic EM3500 EM3561A
Current transformer type	Flexible core

## Complementary

Electrical connection	Flying lead 7.87 ft (2.4 m)600 V
Measurement current	50...5000 A
Network frequency	50 Hz
Frequency measurement range	50...1500 Hz
Measurement accuracy	1 %
Installation category	IV
Pollution degree	2
Thickness	0.31 in (8 mm)
Height	Opened 35.43 in (900 mm)
Diameter	closed 11.30 in (287 mm)

## Environment

IP degree of protection	IP67
Standards	EN 61010-2-032 UL 61010-2-032 ANSI/IEEE C57.13 UL 61010-1

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Oct 22, 2020

	EN 61010-1
Product certifications	UL Recognized CE CURus
Relative humidity	0...95 %
Ambient air temperature for operation	5...140 °F (-15...60 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

### Ordering and shipping details

Category	09661 - POWERLOGIC BASIC CTS
Discount Schedule	PL1
GTIN	03606489421458
Returnability	No

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.