NSYAEDH180S3D

Door hinges for PanelSeT S3D enclosure, door opening: 180°.



M	aı	ır

Range	PanelSeT
Product or Component Type	Hinge
Application	Multi-purpose
Nominal dimensions of the housing	-
Mounting Location	Enclosure
Range compatibility	PanelSeT S3D enclosure
Device composition	Fixing elements 1 x pin 1 x hinge
Quantity per Set	Set of 1

Complementary

Material	Pin aluminium Hinge body zamak	
Fixing mode	By screws - on enclosure body	
Operating angle	180 °	
Maximum load	20 kg/m²	
Net Weight	0.115 lb(US) (0.052 kg)	

Ordering and shipping details

Category	US10ES180036	
Discount Schedule	0ES1	
GTIN	3606480169014	
Returnability	No	
Country of origin	FR	

Packing Units

racking units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.4 in (1 cm)
Package 1 Width	2.0 in (5 cm)
Package 1 Length	3.1 in (8 cm)
Package 1 Weight	1.8 oz (50 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	7.9 in (20 cm)
Package 2 Width	7.9 in (20 cm)
Package 2 Length	11.8 in (30 cm)
Package 2 Weight	11.79 lb(US) (5.35 kg)
Unit Type of Package 3	PAM
Number of Units in Package 3	1000
Package 3 Height	39.4 in (100 cm)
Package 3 Width	39.4 in (100 cm)
Package 3 Length	47.2 in (120 cm)
Package 3 Weight	119.05 lb(US) (54 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months