



### Overview

Presentation	Power Management
Lead time	Usually Ships within 4 Weeks

### Main

Range of Product	Actassi
Product or Component Type	Fixed perforated shelf
Accessory / separate part category	Support accessory
Color	Gray RAL 7035)

### Complementary

Range Compatibility	Actassi VDS Actassi VDA
Material	Sheet steel
Mounting Location	Between the front and rear 19" uprights
Fixing mode	Direct fixing
Number of rack unit	1U
Adjustment	Adjustable from -100 to + 50 mm, in steps of 25 mm
Permanent permissible load	220.5 lb(US) (100 kg)
Distance between centers	18.03 in (458 mm)
Number of rack unit	29U 47U 42U 33U 38U 24U

Enclosure/cubicle description	Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 47.2 in (1200 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 47.2 in (1200 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 55.1 in (1400 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 55.1 in (1400 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 63.0 in (1600 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 63.0 in (1600 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 70.9 in (1800 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 70.9 in (1800 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 78.7 in (2000 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 78.7 in (2000 mm) Enclosure width: 600 mm depth: 31.5 in (800 mm) height: 86.6 in (2200 mm) Enclosure width: 800 mm depth: 31.5 in (800 mm) height: 86.6 in (2200 mm)
-------------------------------	--

Depth	Rack : 23.6 in (600 mm)
-------	-------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480172403
Returnability	Yes
Country of origin	ES

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 in (5 cm)
Package 1 Width	18.5 in (47 cm)
Package 1 Length	24.02 in (61 cm)
Package 1 Weight	9.33 lb(US) (4.23 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	60
Package 2 Height	34.3 in (87 cm)
Package 2 Width	39.4 in (100 cm)
Package 2 Length	48.03 in (122 cm)
Package 2 Weight	588.6 lb(US) (267 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------