NSYDB2015M

Metal industrial cut-out box - low plain cover - H206xW156xD83 - IP55 - grey



Main

Range of Product	PanelSeT SDB
Device Application	Multi-purpose
Product or Component Type	Junction box
Enclosure Type	Empty enclosure
Type of front cover	Low plain cover
Color	Light gray RAL 7035)

Complementary

Complementary		
Enclosure nominal height	8.1 in (206 mm)	
Enclosure nominal width	6.1 in (156 mm)	
Enclosure nominal depth	3.3 in (83 mm)	
Enclosure mounting	Wall mounted	
Device composition	1 body 1 cover 1 cover screw	
Cable entry number	5 0.8 in (20.5 mm) M20) 5 1.004 in (25.5 mm) M25) 5 1.3 in (32.5 mm) M32) 5 1.6 in (40.5 mm) M40)	
Cover fixing	Screw	
Material	steel	
Surface Finish	Epoxy-polyester powder	
Net Weight	2.255 lb(US) (1.023 kg)	

Environment

Standards	IEC 62208
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK07 conforming to IEC 62262

Ordering and shipping details

Category	US10ES180033
Discount Schedule	0ES1
GTIN	3606480187780
Returnability	No
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.346 in (8.500 cm)	
Package 1 Width	6.102 in (15.500 cm)	
Package 1 Length	8.465 in (21.500 cm)	

Package 1 Weight	32.275 oz (915.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	7.087 in (18.000 cm)
Package 2 Width	9.055 in (23.000 cm)
Package 2 Length	17.520 in (44.500 cm)
Package 2 Weight	11.193 lb(US) (5.077 kg)
Unit Type of Package 3	S04
Number of Units in Package 3	10
Package 3 Height	11.811 in (30.000 cm)
Package 3 Width	15.748 in (40.000 cm)
Package 3 Length	23.622 in (60.000 cm)
Package 3 Weight	23.819 lb(US) (10.804 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------