



Main

Category	Mounting accessory
Product or Component Type	Spacer
Range compatibility	PanelSeT CRN PanelSeT S3D PanelSeT S3CM
Application	Multi-purpose
Nominal dimensions of the housing	-
Mounting Location	Switchgear Other hexagonal spacer On mounting plate
Device composition	1 spacer
Quantity per Set	Set of 100
Material	Galvanised steel

Complementary

Fixing mode	Screw-on
Height	1.2 in (30 mm)
ISO thread	M6

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606480181894
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 in (7.5 cm)
Package 1 Width	3.9 in (10.0 cm)
Package 1 Length	5.7 in (14.5 cm)
Package 1 Weight	0.5 oz (15.0 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	3.0 in (7.5 cm)
Package 2 Width	3.9 in (10.0 cm)
Package 2 Length	5.7 in (14.5 cm)
Package 2 Weight	3.3 lb(US) (1.5 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------