



Main

Range	Thalassa
Accessory / separate part category	Connection accessory
Product or Component Type	Cable connector
Application	Cable installation
Additional information	With strain relief
Line Rated Current	16 A
Rated voltage	250 V
Network type	AC

Complementary

Connector Type	Male
Material	Polyamide
Body colour	Black
Fixing mode	Screw
Cable outer diameter	0.2...0.4 in (5.5...9 mm)
Nominal cross section	0.0008...0.004 in ² (0.5...2.5 mm ²)
Cable cross section	0.0008...0.004 in ² (0.5...2.5 mm ²)
Height	0.5 in (13.8 mm)
Width	0.9 in (23 mm)
Depth	2.09 in (53.2 mm)
IP degree of protection	IP20

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606489550820
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.4 in (3.5 cm)
Package 1 Width	4.9 in (12.5 cm)
Package 1 Length	2.8 in (7.0 cm)
Package 1 Weight	0.2 oz (5.0 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information