Product data sheet

Specification





Portable lamp with on/off switch - 230V AC - 10W

NSYLAMPORTLD

Product availability: Stock - Normally stocked in distribution

facility

Price*: 124.29 USD

Main

| Range Of Product | Lighting and power sockets | |
|--|-----------------------------------|--|
| accessory / Separate Part Lighting accessory | | |
| Product Or Component Type | Lamp | |
| Device Application | Multi-purpose | |
| Device Composition | 1 lamp 1 cable 1 fixed base | |
| Power Factor | 0.9 | |

Complementary

| Outlet Standard | Without socket | |
|--------------------------------|------------------------------|--|
| Rated Lamp Wattage | 10 W | |
| [Ue] Rated Operational Voltage | 120 V AC 50/60 Hz | |
| Bulb Base | E27 | |
| Bulb Type | LED | |
| Control Type | Built-in recessed switch | |
| Luminous Flux | 1100 lm | |
| Colour Temperature | 4000 K | |
| Service Life In Hours | 25000 h | |
| Electrical Connection | Cable 9.84 ft (3 m) supplied | |
| Fixing Mode | Screws Adhesive | |
| Range Compatibility | Spacial Thalassa | |
| Material | PC (UL94 V-0) | |
| Height | 15.89 in (403.5 mm) | |
| Width | 3.60 in (91.5 mm) | |
| Depth | 2.60 in (66 mm) | |
| Color | Black RAL 9005) | |

Environment

| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
|-----------------------------|------------------------------|
| Flectrical Insulation Class | Class II |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Standards | IEC 60598 UL 94 |
|---------------------------------------|---------------------|
| Ambient Air Temperature For Operation | 3149 °F (-1665 °C) |
| Ambient Air Temperature For | 14140 °F (-1060 °C) |

Ordering and shipping details

| Category | 80036-ENCLOSURE SYSTEMS ACCESSORIES |
|-------------------|-------------------------------------|
| Discount Schedule | ES1 |
| Gtin | 3606481190390 |
| Returnability | No |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 3.35 in (8.5 cm) |
| Package 1 Width | 4.33 in (11.0 cm) |
| Package 1 Length | 14.57 in (37.0 cm) |
| Package 1 Weight | 31.11 oz (882.0 g) |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 9.45 in (24.0 cm) |
| Package 2 Width | 14.96 in (38.0 cm) |
| Package 2 Length | 16.73 in (42.5 cm) |
| Package 2 Weight | 20.75 lb(US) (9.41 kg) |



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ② | Toxic Heavy Metal Free | |
| Ø | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |