



### Main

| Product or Component Type | Key |
|---------------------------|-----|
|---------------------------|-----|

### Complementary

|                                    |                      |
|------------------------------------|----------------------|
| Accessory / separate part category | Locking accessory    |
| Accessory / separate part type     | Key for shape insert |
| Device Application                 | Multi-purpose        |
| Range compatibility                | Thalassa<br>PanelSeT |
| Device composition                 | 1 key                |
| Quantity per Set                   | Set of 1             |
| Lock type                          | Lock 5 mm double bar |

### Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10ES180036  |
| Discount Schedule | 0ES1          |
| GTIN              | 3606480310041 |
| Returnability     | Yes           |
| Country of origin | ES            |

### Packing Units

|                              |                            |
|------------------------------|----------------------------|
| Unit Type of Package 1       | PCE                        |
| Number of Units in Package 1 | 1                          |
| Package 1 Height             | 0.591 in (1.500 cm)        |
| Package 1 Width              | 1.969 in (5.000 cm)        |
| Package 1 Length             | 3.543 in (9.000 cm)        |
| Package 1 Weight             | 1.658 oz (47.000 g)        |
| Unit Type of Package 2       | P12                        |
| Number of Units in Package 2 | 1200                       |
| Package 2 Height             | 17.717 in (45.000 cm)      |
| Package 2 Width              | 31.496 in (80.000 cm)      |
| Package 2 Length             | 47.244 in (120.000 cm)     |
| Package 2 Weight             | 156.531 lb(US) (71.001 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product                                      |
| REACH Regulation           | <a href="#">REACH Declaration</a>                          |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                     |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>              |
| Circularity Profile        | No need of specific recycling operations                   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|