

# Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, plain door, open bottom, 1000x500x420mm, IP54, IK10

NSYPLAZ1054G

Product availability: Stock - Normally stocked in distribution facility

**Price\*: 1,112.80 USD**

## Main

Range	Thalassa
Product Name	Thalassa PLA
Enclosure Type	Multi-purpose
Product Or Component Type	Suitable enclosure
Version	PLAZ
Nominal Height	39.37 in (1000 mm)
Nominal Width	19.69 in (500 mm)
Nominal Depth	16.54 in (420 mm)
Enclosure Mounting	Floor-standing
Device Composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 plinth

## Complementary

Body Type	Sealed top and open bottom part assembled with side parts
Door Type	Solid front
Number Of Doors	1
Door Opening Side	Reversible 120 °)
Lock Type	4 points lock, handle with 5 mm double bar insert
Accessibility For Operation	Rear Front Bottom
Removable Parts	Door by hinges Rear panel by fixing element
Material	polyester reinforced with fibreglass
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	Veritas
Electrical Insulation Class	Class II

## Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ip Degree Of Protection</b>	IP54 IEC 60529 plinth type open bottom)
<b>Ik Degree Of Protection</b>	IK10 IEC 62262 plain door)
<b>Fire Resistance</b>	1760 °F (960 °C) IEC 62208
<b>Ambient Air Temperature For Storage</b>	-31...194 °F (-35...90 °C)

## Ordering and shipping details

<b>Category</b>	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
<b>Discount Schedule</b>	ES1
<b>Gtin</b>	3606480775604
<b>Returnability</b>	No
<b>Country Of Origin</b>	ES

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	42.13 in (107.0 cm)
<b>Package 1 Width</b>	21.26 in (54.0 cm)
<b>Package 1 Length</b>	18.90 in (48.0 cm)
<b>Package 1 Weight</b>	61.80 lb(US) (28.032 kg)
<b>Unit Type Of Package 2</b>	PAL
<b>Number Of Units In Package 2</b>	4
<b>Package 2 Height</b>	49.61 in (126 cm)
<b>Package 2 Width</b>	39.37 in (100 cm)
<b>Package 2 Length</b>	47.64 in (121 cm)
<b>Package 2 Weight</b>	255.74 lb(US) (116 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

RoHS Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)

China RoHS Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations