

# Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, open bottom, ventilated canopy, 1250x1250x620mm, IP44, IK10

NSYPLAZT12126G

Product availability: Stock - Normally stocked in distribution facility

**Price\*: 2,590.23 USD**

## Main

Range	Thalassa
Product Name	Thalassa PLA
Enclosure Type	Multi-purpose
Product Or Component Type	Suitable enclosure
Version	PLAZT
Nominal Height	49.21 in (1250 mm)
Nominal Width	49.21 in (1250 mm)
Nominal Depth	24.41 in (620 mm)
Enclosure Mounting	Floor-standing
Device Composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel 1 canopy 1 plinth

## Complementary

Body Type	Open top and bottom part assembled with side parts
Door Type	Solid front
Number Of Doors	2
Door Opening Side	Right and left 180 °)
Lock Type	4 points lock, handle with 5 mm double bar insert
Accessibility For Operation	Rear Top Front Bottom
Removable Parts	Door by hinges Rear panel by fixing element Canopy by fixing element
Material	polyester reinforced with fibreglass
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	Veritas
Electrical Insulation Class	Class II

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

<b>Ip Degree Of Protection</b>	IP44 IEC 60529 with plinth type open bottom part and ventilated canopy)
<b>Ik Degree Of Protection</b>	IK10 IEC 62262 plain door)
<b>Fire Resistance</b>	1760 °F (960 °C) IEC 62208
<b>Ambient Air Temperature For Storage</b>	-31...194 °F (-35...90 °C)

## Ordering and shipping details

<b>Category</b>	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
<b>Discount Schedule</b>	ES1
<b>Gtin</b>	3606480772887
<b>Returnability</b>	No
<b>Country Of Origin</b>	ES

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	51.18 in (130.0 cm)
<b>Package 1 Width</b>	26.77 in (68.0 cm)
<b>Package 1 Length</b>	50.39 in (128.0 cm)
<b>Package 1 Weight</b>	167.55 lb(US) (76.0 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations