

Product data sheet

Specifications



Floor standing polyester enclosure, Thalassa PLA, open bottom, ventilated canopy, 750x750x320mm, IP44, IK10

NSYPLAZT773G

Product availability: Stock - Normally stocked in distribution facility

Price*: 836.90 USD

Main

| | |
|---------------------------|--|
| Range | Thalassa |
| Product Name | Thalassa PLA |
| Enclosure Type | Multi-purpose |
| Product Or Component Type | Suitable enclosure |
| Version | PLAZT |
| Nominal Height | 29.53 in (750 mm) |
| Nominal Width | 29.53 in (750 mm) |
| Nominal Depth | 12.60 in (320 mm) |
| Enclosure Mounting | Floor-standing |
| Device Composition | 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 canopy 1 plinth |

Complementary

| | |
|-----------------------------|--|
| Body Type | Open top and bottom part assembled with side parts |
| Door Type | Solid front |
| Number Of Doors | 1 |
| Door Opening Side | Reversible 180 °) |
| Lock Type | 2 points handle lock, 5 mm double-bar |
| Accessibility For Operation | Front Rear Top Bottom |
| Removable Parts | Door by hinges Rear panel by fixing element Canopy by fixing element |
| Material | polyester reinforced with fibreglass |
| Color | Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | Veritas |
| Electrical Insulation Class | Class II |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| | |
|--|---|
| Ip Degree Of Protection | IP44 IEC 60529 with plinth type open bottom part and ventilated canopy) |
| Ik Degree Of Protection | IK10 IEC 62262 plain door) |
| Fire Resistance | 1760 °F (960 °C) IEC 62208 |
| Ambient Air Temperature For Storage | -31...194 °F (-35...90 °C) |

Ordering and shipping details

| | |
|--------------------------|--|
| Category | 80034-ENCLOSURE SYSTEMS WALL MOUNT METAL |
| Discount Schedule | ES1 |
| Gtin | 3606480776335 |
| Returnability | No |
| Country Of Origin | ES |

Packing Units

| | |
|-------------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 32.68 in (83.0 cm) |
| Package 1 Width | 30.71 in (78.0 cm) |
| Package 1 Length | 14.96 in (38.0 cm) |
| Package 1 Weight | 59.52 lb(US) (27.0 kg) |
| Unit Type Of Package 2 | PAM |
| Number Of Units In Package 2 | 6 |
| Package 2 Height | 47.24 in (120 cm) |
| Package 2 Width | 39.37 in (100 cm) |
| Package 2 Length | 72.05 in (183 cm) |
| Package 2 Weight | 379.20 lb(US) (172 kg) |

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations