

# Product data sheet

Specifications



Wall mounted ABS + PC enclosure, Thalassa PLM, plain door, with bakelite plate, 310x215x160mm, IP66, IK10, RAL 7035

NSYPLM32BG

Product availability: Stock - Normally stocked in distribution facility

**Price\*: 112.56 USD**

## Main

Range	Thalassa
Product Name	Thalassa PLM
Device Short Name	PLM
Enclosure Type	Multi-purpose
Category	Compact enclosure
Nominal Height	12.20 in (310 mm)
Nominal Width	8.46 in (215 mm)
Nominal Depth	6.30 in (160 mm)
Enclosure Mounting	Wall mounted
Device Composition	1 body 1 door 1 lock 1 mounting plate
Door Type	Solid
Lock Type	3 mm double-bar lock

## Complementary

Number Of Locks	1
Mounting Plate Description	Plain bakelite
Accessibility For Operation	Front
Removable Parts	Door by hinges Mounting plate by fixing element
Material	ABS + PC
Color	Gray RAL 7035)
Standards	NEMA classification 13 IEC 62208 NEMA classification 4X
Product Certifications	UL
Electrical Insulation Class	Class II

## Environment

Ip Degree Of Protection	IP66 IEC 60529
-------------------------	----------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ik Degree Of Protection</b>	IK10 IEC 62262
<b>Fire Resistance</b>	1760 °F (960 °C) IEC 62208
<b>Ambient Air Temperature For Operation</b>	-40...176 °F (-40...80 °C)

## Ordering and shipping details

<b>Category</b>	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
<b>Discount Schedule</b>	ES1
<b>Gtin</b>	3606480776489
<b>Returnability</b>	No
<b>Country Of Origin</b>	ES

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	9.00 in (22.86 cm)
<b>Package 1 Width</b>	7.00 in (17.78 cm)
<b>Package 1 Length</b>	12.50 in (31.75 cm)
<b>Package 1 Weight</b>	3.70 lb(US) (1.68 kg)
<b>Unit Type Of Package 2</b>	P12
<b>Number Of Units In Package 2</b>	70
<b>Package 2 Height</b>	47.24 in (120 cm)
<b>Package 2 Width</b>	31.50 in (80 cm)
<b>Package 2 Length</b>	50.79 in (129 cm)
<b>Package 2 Weight</b>	284.40 lb(US) (129 kg)

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations