NSYPLM32TG

Wall mounted ABS + PC enclosure, Thalassa PLM, glazed door, 310x215x160mm, IP66, IK10, RAL 7035



Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	12.2 in (310 mm)
Nominal width	8.5 in (215 mm)
Nominal depth	6.3 in (160 mm)
Enclosure mounting	Wall mounted
Device composition	1 body 1 door 1 lock
Door type	Transparent
Lock type	3 mm double-bar lock

Complementary

Number of locks	1	
Mounting plate description	Without mounting plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Door polycarbonate Body ABS + PC	
Color	Gray RAL 7035)	
Standards	NEMA classification 13 NEMA classification 4X IEC 62208	
Electrical Insulation Class	Class II	

Environment

IP degree of protection	IP66 IEC 60529	
IK degree of protection	IK10 IEC 62262	
Fire resistance	1760 °F (960 °C) IEC 62208	
Ambient Air Temperature for Operation	-40176 °F (-4080 °C)	

Ordering and shipping details

Category	US10ES180034
Discount Schedule	0ES1
GTIN	3606480776502
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.693 in (17.000 cm)
Package 1 Width	9.055 in (23.000 cm)
Package 1 Length	12.598 in (32.000 cm)
Package 1 Weight	3.263 lb(US) (1.480 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	70
Package 2 Height	51.181 in (130.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	241.406 lb(US) (109.500 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations