

# NSYS3D121230D

Wall mounted steel enclosure, PanelSeT S3D,  
double plain door, without mounting plate,  
1200x1200x300mm, IP55, IK10



## Main

Range	PanelSeT
Product name	PanelSeT S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	47.2 in (1200 mm)
Enclosure nominal width	47.2 in (1200 mm)
Enclosure nominal depth	11.8 in (300 mm)
Door type	Solid
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate 1 lock 2 door

## Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness
Number of doors	Front face 2
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws
Material	steel
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	DNV[RETURN]GL[RETURN]cUL[RETURN]UL[RETURN]BV
Net Weight	130.07 lb(US) (59 kg)

## Environment

Electromagnetic compatibility	Electromagnetic field immunity test
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP55 IEC 60529

## Ordering and shipping details

Category	US10ES180034
Discount Schedule	0ES1
GTIN	3606480159985
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.8 in (35.0 cm)
Package 1 Width	47.2 in (120.0 cm)
Package 1 Length	48.2 in (122.5 cm)
Package 1 Weight	132.3 lb(US) (60.0 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	2
Package 2 Height	53.9 in (137.0 cm)
Package 2 Width	31.5 in (80.0 cm)
Package 2 Length	47.2 in (120.0 cm)
Package 2 Weight	299.8 lb(US) (136.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------