

NSYS3D121230DP

Wall mounted steel enclosure, PanelSeT S3D, double plain door, with mounting plate, 1200x1200x300mm, IP55, IK10



Main

| | |
|-----------------------------|---|
| Range | PanelSeT |
| Product name | PanelSeT S3D |
| Application | Multi-purpose |
| Category | Compact enclosure |
| Enclosure nominal height | 47.2 in (1200 mm) |
| Enclosure nominal width | 47.2 in (1200 mm) |
| Enclosure nominal depth | 11.8 in (300 mm) |
| Door type | Solid |
| Mounting plate description | Plain |
| Type of gland plate | Standard |
| Installation accessory type | Wall-mounting |
| Device composition | 1 body 2 cable gland plate 2 door with lock 1 mounting plate |

Complementary

| | |
|-----------------------------|---|
| Body type | Gutter-shaped front rail double sheet thickness Single piece body |
| Number of doors | Front face 2 |
| Door opening side | Reversible 120 °) |
| Lock type | 3 points lock, 3 mm double-bar |
| Accessibility for operation | Front |
| Removable parts | Door by hinges Cable gland plate by screws Mounting plate by fixing element |
| Material | Enclosure steel Mounting plate galvanised steel |
| Surface finish | Enclosure epoxy-polyester powder |
| Color | Enclosure Gray RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | UL[RETURN]cUL[RETURN]GL[RETURN]BV[RETURN]DNV |
| Net Weight | 189.6 lb(US) (86 kg) |

Environment

| | |
|-------------------------|----------------|
| IK degree of protection | IK10 IEC 62262 |
| IP degree of protection | IP55 IEC 60529 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US10ES180034 |
| Discount Schedule | 0ES1 |
| GTIN | 3606480159978 |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.0 in (35.5 cm) |
| Package 1 Width | 47.2 in (120.0 cm) |
| Package 1 Length | 48.2 in (122.5 cm) |
| Package 1 Weight | 189.6 lb(US) (86.0 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 54.3 in (138.0 cm) |
| Package 2 Width | 31.5 in (80.0 cm) |
| Package 2 Length | 48.2 in (122.5 cm) |
| Package 2 Weight | 412.3 lb(US) (187.0 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|